



COUNTRY COLOUR

Variety of colours and unsurpassed durability – for all weather conditions!



PRODUCT DESCRIPTION

Opaque, at first slightly satin-gloss then satin finish based on natural oils for exterior wood.

Microporous surface allows the wood to breathe and reduces swelling and shrinkage. Water-repellent, extremely weather-resistant and UV-stable surface does not crack, peel, flake or blister.

No sanding necessary, just simply recoat; no primer is needed. Easy and seamless application. Finish stays workable while coating.

When dry, finish is safe for humans, animals and plants and is suitable for children's toys as per EN 71.3 (European norm) and is saliva-resistant and sweatproof according to DIN 53160 (German industrial norm).

Wood tone and grain is covered. The structure of the wood remains noticeable.

RECOMMENDED USE

Osmo Country Colour is best suited for any exterior wood where an especially durable coating is required: timber cladding, balconies, windows and window shutters, fences, pergolas, wooden shingles, garden furniture and summer houses, carports etc. Ideal for recoating old microporous finishes and weathered wooden surfaces.

INGREDIENTS

Based on natural plant oils (sunflower oil, soya oil, thistle oil and linseed oil), iron oxide and organic pigments, titanium dioxide white pigment, siccatives (drying agents) and water-repellent additives. Deaeromatized white spirit (benzene-free). This product fulfils EU regulations (2004/42/EC) according to the VOC content of max. 400 g/l (Cat. A/e (2010)).

Detailed declaration of ingredients available upon request.

TECHNICAL DATA

Specific gravity: 1.0-1.35 g/cm³

Viscosity: 20-60s DIN EN ISO 2431/4 mm, viscid

Odour: faint/mild, after drying odourless

Flash point: >60°C acc. DIN EN ISO 2719



STORAGE

Up to 5 years and longer if can is kept dry and closed tightly. If thickened by frost, store for 24-36 hours at room temperature before use.

SURFACE PREPARATION

Wood surface must be clean, dry and frost-free (moisture content max. 20%).

Osmo Country Colour is ready to use, please do not thin. Stir well before use.

Clean old microporous stains thoroughly. Old paints and lacquers must be completely removed. As a general rule, wear a dust mask during sanding works.

If possible, please apply the first coat to all sides before installation.

The finished surface is, among other things, influenced by the wood's natural characteristics. Therefore, a trial application is always required, especially for unfamiliar surfaces.

If additional protection against blue stain, rot and insects is desired, pre-treat the wood if possible on all sides with Osmo WR Base Coat*.

Before recoating, allow to dry for 12-24 hours.

*Use biocides safely. Always read label and product information before use.

METHODS OF APPLICATION

Apply thinly and evenly to the clean and dry wood along the wood grain with Osmo Natural Bristle Brush or Osmo Microfibre Roller and spread well.

Allow to dry for approx. 10-12 hours with good ventilation.

After drying, apply a second coat – also thinly.

When renovating, one coat applied to the clean and dry surface is usually sufficient.

CLEANING OF TOOLS

With Osmo Brush Cleaner (free of aromatic compounds).

DRYING TIME

Approx. 10-12 hours (normal climatic conditions, 23 °C/50 % rel. humidity). Lower temperatures and/or higher air humidity can increase the drying time. Allow for good ventilation while drying.

COVERAGE

1 litre covers approx. 26 m² with one coat.

Product coverage depends significantly on the character of the wood. All information refers to smooth and planed/cut surfaces. Other surfaces may lead to reduced coverage.

NOTE

If exterior surfaces (e.g. windows, cladding) should have extra protection, apply one final top coat of Osmo UV-Protection-Oil Extra Clear (410 without film protection or 420 with film protection) after thoroughly drying. This protects against dirt and stains and extends the life of the finish. For Country Colour White 2101, please use Natural Oil Woodstain White 900.

Country Colour has been tried and trusted over decades and is also available in custom colours. Starting from 2.5 litres per colour tone, available in 186 RAL Classic and 1950 NCS colour tones, as well as with biocidal film protection additives.

Many wood species contain water-soluble coloured extractives which may leach out naturally when weathered.

CAUTION

Keep out of reach of children. Do not get in eyes, on skin, or on clothing. Contains 2-butanonoxime. May produce an allergic reaction. If medical advice is needed, have product container or label at hand. Use only outdoors or in a well-ventilated area. Dispose of contents/container in accordance with chemical waste disposal regulations (AVV 08 01 11). Warning: Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition). The dried finish is classified as B2 (normal flammability) according to DIN 4102 regulations.

Safety data sheet upon request.

DISPOSAL

Dispose of leftover product and completely emptied packaging according to local official guidelines (waste code number 08 01 11). Only completely emptied cans can be recycled.

COLOUR TONES

- 2101 White
- 2203 Light Ochre
- 2204 Ivory
- 2205 Sunflower Yellow
- 2308 Nordic Red
- 2310 Cedar/Redwood
- 2311 Signal Red
- 2404 Fir Green
- 2501 Labrador Blue
- 2506 Royal Blue
- 2507 Dove Blue
- 2606 Medium Brown
- 2607 Dark Brown
- 2703 Charcoal



2704 Dusk Grey
2708 Pebble Grey
2716 Anthracite Grey
2735 Light Grey
2742 Traffic Grey

CAN SIZES

0.75 L; 2.50 L; 25 L

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 06/15