

Material Safety Data Sheets
 according to 1907/2006/EC, Article 31

Printing date 15.09.2016

Version number 1

Revision: 15.09.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Osmo Polyx®-Oil Express

Article number: 3332 Clear Satin
 3362 Clear Matt

1.2 Relevant identified uses of the substance or mixture and uses advised against

advised against No further relevant information available.

Application of the substance / the mixture

Coating compound/ Surface coating/ paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG
 Affhüppen Esch 12
 D-48231 Warendorf

Further information obtainable from:

Product safety department
 Phone: +49 (0) 251 / 692 - 188
 Fax: +49 (0) 251 / 692 - 462
 e-mail: helmut.starp@osmo.de

1.4 Emergency telephone number:

emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German and English

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

2.2 Label elements

Labelling according to Regulation

(EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02

Signal word

Warning

Hazard statements

H226 Flammable liquid and vapour.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P210 Keep away from heat/open flames. - No smoking.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves / eye protection.
 P262 Do not get in eyes, on skin, or on clothing.

(Contd. on page 2)

Material Safety Data Sheets
 according to 1907/2006/EC, Article 31

Printing date 15.09.2016

Version number 1

Revision: 15.09.2016

Trade name: Osmo Polyx®-Oil Express

(Contd. of page 1)

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****3.2 Mixtures****Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

CAS: 64742-48-9 918-481-9 Index number: 649-327-00-6 Reg.nr.: 01-2119457273-39	aliphatic hydrocarbons, C10-C13 ----- ⚠ Asp. Tox. 1, H304	25-50%
CAS: 64742-49-0 927-241-2 Index number: 649-328-00-1 Reg.nr.: 01-2119471843-32	aliphatic hydrocarbons, C9-C10 ----- ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ STOT SE 3, H336; Aquatic Chronic 3, H412	10-<25%
CAS: 34590-94-8 EINECS: 252-104-2 Reg.nr.: 01-2119450011-60	(2-methoxymethylethoxy)propanol substance with a Community workplace exposure limit	0.1-≤2.5%

Additional information: For the wording of the listed hazard phrases refer to section 16.**SECTION 4: First aid measures****4.1 Description of first aid measures****General information:** Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

After skin contact:

In case of unconsciousness place patient stably in side position for transportation.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

If swallowed, seek medical advice immediately and show this container or label.

4.2 Most important symptoms and**effects, both acute and delayed**

Headache

Dizziness

(Contd. on page 3)

Material Safety Data Sheets
according to 1907/2006/EC, Article 31

Printing date 15.09.2016

Version number 1

Revision: 15.09.2016

Trade name: Osmo Polyx®-Oil Express

(Contd. of page 2)

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents:

Water with full jet

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters**Protective equipment:**

Mouth respiratory protective device.

Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

Ensure adequate ventilation

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

Ensure adequate ventilation.

Warm water and cleansing agent

6.4 Reference to other sections

See Section 13 for disposal information.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Keep away from heat and direct sunlight.

Keep receptacles tightly sealed.

Use only in well ventilated areas.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Protect against electrostatic charges.

(Contd. on page 4)

Material Safety Data Sheets
 according to 1907/2006/EC, Article 31

Printing date 15.09.2016

Version number 1

Revision: 15.09.2016

Trade name: Osmo Polyx®-Oil Express

(Contd. of page 3)

Keep ignition sources away - Do not smoke.

7.2 Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by****storerooms and receptacles:**

Store in a cool location.

Store only in the original receptacle.

Information about storage in one**common storage facility:**

Do not store together with alkalis (caustic solutions).

Do not store together with oxidising and acidic materials.

Further information about**storage conditions:**

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Storage class:

3

7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about**design of technical facilities:**

No further data; see item 7.

8.1 Control parameters**Ingredients with limit values that require monitoring at the workplace:****64742-48-9 aliphatic hydrocarbons, C10-C13**

TWA (8 H)	Long-term value: 1.000 mg/m ³ , 150 ppm ppm
	Source: UK SIA

34590-94-8 (2-methoxymethylethoxy)propanol

WEL	Long-term value: 308 mg/m ³ , 50 ppm
	Sk

Additional information:

The lists valid during the making were used as basis.

8.2 Exposure controls**Personal protective equipment:****General protective and hygienic****measures:**

Immediately remove all soiled and contaminated clothing

Keep away from foodstuffs, beverages and feed.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

Respiratory protection:

Not necessary if room is well-ventilated.

Use suitable respiratory protective device only when aerosol or mist is formed.

Protection of hands:

Protective gloves

(Contd. on page 5)

Material Safety Data Sheets
 according to 1907/2006/EC, Article 31

Printing date 15.09.2016

Version number 1

Revision: 15.09.2016

Trade name: Osmo Polyx®-Oil Express

(Contd. of page 4)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Eye protection:

Tightly sealed goggles

Body protection:

Protective work clothing

SECTION 9: Physical and chemical properties
9.1 Information on basic physical and chemical properties
General Information
Appearance:**Form:** Fluid**Colour:** Grey**Odour:** Mild**Change in condition****Melting point/Melting range:** Undetermined.**Boiling point/Boiling range:** Undetermined.**Flash point:** 30-35 °C (DIN 53213)**Self-igniting:** Product is not selfigniting.

Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Explosion limits:**Lower:** 0.6 Vol %**Upper:** 7.0 Vol %**Vapour pressure at 20 °C:** 10 hPa**Density at 20 °C:** 0.88-0.95 g/cm³ (DIN 51757)
Solubility in / Miscibility with water:

Not miscible or difficult to mix.

(Contd. on page 6)

Material Safety Data Sheets
 according to 1907/2006/EC, Article 31

Printing date 15.09.2016

Version number 1

Revision: 15.09.2016

Trade name: Osmo Polyx®-Oil Express

(Contd. of page 5)

Viscosity:

Dynamic: Not determined.
Kinematic at 20 °C: 20-25 s (DIN 53211/4)

Solvent content:

VOC (EC) < 500 g/l (VOC-max. Cat A/i (2010) = 500 g/l)
9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.
10.2 Chemical stability
Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
10.3 Possibility of hazardous reactions Reacts with fabric soaked in the product (e.g. cleaning wool).
10.4 Conditions to avoid No further relevant information available.
10.5 Incompatible materials: No further relevant information available.
10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide
 Nitrogen oxides (NOx)
Additional information: Warning:
 Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)

SECTION 11: Toxicological information

11.1 Information on toxicological effects
Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:
64742-48-9 aliphatic hydrocarbons, C10-C13

Oral	LD50	> 5000 mg/kg (rat) (OECD 401)
Dermal	LD50	> 5000 mg/kg (rat) (OECD 402)
Inhalative	LC50 / 4h	21 mg/l (rat) (OECD 403)

64742-49-0 aliphatic hydrocarbons, C9-C10

Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50 / 4h	>20 mg/l (rat)

(Contd. on page 7)

Material Safety Data Sheets
 according to 1907/2006/EC, Article 31

Printing date 15.09.2016

Version number 1

Revision: 15.09.2016

Trade name: Osmo Polyx®-Oil Express

(Contd. of page 6)

34590-94-8 (2-methoxymethylethoxy)propanol

Oral	LD50	> 5000 mg/kg (rat)
Dermal	LD50	> 2000 mg/kg (rat)
		13000 - 14000 mg/kg (rabbit)
Inhalative	LC50 / 4h	500 mg/l (rat)
	LC50 / 72h	0.76 mg/l (senastrum capricornutum)

Primary irritant effect:

Skin corrosion/irritation At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information**12.1 Toxicity****Aquatic toxicity:****64742-48-9 aliphatic hydrocarbons, C10-C13**

EC50 / 48h	> 1000 mg/l (daphnia) (OECD 202)
EC50/ 72h	> 1000 mg/l (algae) (OECD 201)
LC50 / 96h	> 1000 mg/l (fish) (OECD 203)
Biolog. Abbaubarkeit	(leicht abbaubar)

64742-49-0 aliphatic hydrocarbons, C9-C10

EC50 / 24h	<130 mg/kg (Oncorhynchus mykiss (Regenbogenforelle)) >100 mg/kg (senastrum capricornutum)
------------	--

34590-94-8 (2-methoxymethylethoxy)propanol

EC50 / 48h (Static)	1919 mg/l (daphnia)
LC50 / 96h	5.3 mg/l (Oncorhynchus mykiss (Regenbogenforelle))
LC50 / 48h	10.2 mg/l (Oncorhynchus mykiss (Regenbogenforelle))

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

(Contd. on page 8)

Material Safety Data Sheets
according to 1907/2006/EC, Article 31

Printing date 15.09.2016

Version number 1

Revision: 15.09.2016

Trade name: Osmo Polyx®-Oil Express

(Contd. of page 7)

Additional ecological information:

General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow product to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment**PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Other adverse effects** No further relevant information available.**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
15 01 10*	packaging containing residues of or contaminated by hazardous substances

Uncleaned packaging:**Recommendation:** Disposal must be made according to official regulations.**Recommended cleansing agents:** Solvent naphtha**SECTION 14: Transport information****14.1 UN-Number****ADR, IMDG, IATA** UN1263**14.2 UN proper shipping name****ADR** 1263 PAINT**IMDG** PAINT**IATA** Paint**14.3 Transport hazard class(es)****ADR****Class** 3 (F1) Flammable liquids.**Label** 3**IMDG, IATA****Class** 3 Flammable liquids.**Label** 3**14.4 Packing group****ADR, IMDG, IATA** III

(Contd. on page 9)

Trade name: Osmo Polyx®-Oil Express

(Contd. of page 8)

14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	
Danger code (Kemler):	Warning: Flammable liquids. 30
EMS Number:	F-E, <u>S-E</u>
Stowage Category	A
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	
	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information
15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
Directive 2012/18/EU
Named dangerous substances -
ANNEX I

None of the ingredients is listed.

Seveso category

P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements

5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements

50,000 t

REGULATION (EC) No
1907/2006 ANNEX XVII

Conditions of restriction: 3, 55

(Contd. on page 10)

Material Safety Data Sheets
 according to 1907/2006/EC, Article 31

Printing date 15.09.2016

Version number 1

Revision: 15.09.2016

Trade name: Osmo Polyx®-Oil Express

(Contd. of page 9)

National regulations:

VOC (EC) < 500 g/l (VOC-max. = 500 g/l (2010 A/i))

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting effects.

Department issuing SDS:

product safety department

Contact:

Hr. Dr. Starp

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Flam. Liq. 3: Flammable liquids – Category 3
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 Asp. Tox. 1: Aspiration hazard – Category 1
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3