



# Full declaration of ingredients

## 2K Wood Oil

### Component A

**Binding agents:**

- Based on the renewable plant raw materials: Linseed oil and linseed oil varnish

**Solvents:**

- Solvent free – Full Solid

**Pigments:** (except 6100)

- Mineral pigments on the basis of ore; titanium dioxide and iron oxides (yellow, red, brown, black)
- Organic pigments (yellow, red, green, blue) which are in compliance with German Industrial Norm DIN 53160 (fast to perspiration and saliva) and Euro Norm EN 71.3 (safety of children's toys)

**Additives:**

- Siccatives (are obtained from the respective minerals and are lead-free)
- Ketoximes
- Waxes

The listed ingredients serve to regulate the drying process and to prevent film formation.

### Component B

**Hardener:**

- Solvent-free, aliphatic polyisocyanate  
<0.1% free diisocyanate

Contains isocyanates. Follow the manufacturer's instructions. When handling, observe the technical rules for hazardous substances TRGS 430 "Isocyanate risk assessment and protective measures". In the workplace, isocyanates can mainly enter the body through the respiratory tract, but also through the skin. When inhaling vapours or spray mist, there is a risk of sensitization. When handling isocyanate-containing paints, carefully observe all measures for solvent-based paints. In particular, do not inhale spray mist and vapours. Allergy sufferers, asthmatics and persons prone to respiratory diseases are not allowed to work with isocyanate-containing paints.

Further information, e.g. for the technical characteristics, please refer to the product information.

*The above mentioned information is provided to the best of our knowledge however without any liability.  
(Version 01/2021)*