PRODUCT INFORMATION
EXTERIOR OIL WOODSTAIN CLEAR



701 Clear Matt





PRODUCT DESCRIPTION:

.

INGREDIENTS:

Binding agent based on natural plant oils (sunflower oil, soybean oil, thistle oil and linseed oil), siccatives (drying agents) and additives. Biocidal active ingredient: 3-iodo-2-propynyl butylcarbamate (IPBC). Dearomatised white spirit (benzene-free). Detailed declaration of ingredients available upon request.

TECHNICAL DATA:

Specific weight: 0.970-1.000 g/cm³ (DIN ISO 2811-2)
Viscosity: 25-35s (DIN 53211/4mm)
Odour: faint/mild, odourless after drying
Flashpoint: >60°C (DIN EN ISO 2719)

STORAGE:

5 years or longer if stored in the originally closed container. If thickened by frost, store at room temperature for 24 hours prior to use.

The finished surface and the product coverage are influenced by several factors, including the condition of the wood. Therefore, a trial application is always required, especially for unfamiliar surfaces.

CLEANING OF TOOLS:

With Osmo Brush Cleaner (free of aromatic compounds).

DRYING TIME:

Approx. 12 hours (normal climatic conditions, 20-23°C / 50-65 % rel. humidity). Ventilate well while drying. Lower temperatures and/or higher air humidity may increase drying times significantly.

COVERAGE:

Product coverage for 1 coat is 26 m²/1 l. It depends significantly on the condition of the wood. All information refers to smooth and planed/cut surfaces. Other surfaces may lead to deviations in coverage.

CAUTION:

Harmful to aquatic life with long lasting effects. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Avoid release to the environment. Contains 3-Iodo-2-propynylbutylcarbamate (film protection). May produce an allergic reaction. Warning: Materials impregnated with liquid product, such as cloths, may self-ignite. After use, let the materials to dry completely either spread out flat or in a closed metal container and then dispose of them properly. EU limit value for this product (cat. A/e): 400 g/l VOC. This product contains max. 400 g/l VOC.

Always follow the information on the product label.

DISPOSAL:

Dispose of product residuals according to the official guidelines (European Waste Code (EWC)-Code 08 01 11*). Only completely emptied containers can be recycled.

COLOUR TONE:

701 Clear Matt

Osmo Holz und Color GmbH & Co. KG | Affhüppen Esch 12, D-48231 Warendorf | Postfach 110161 | D-48203 Warendorf
Telefon +49 (0) 25 81 / 9 22-100 | Telefax +49 (0) 25 81 / 9 22-200 | info@osmo.de | **www.osmo.com**

PRODUCT INFORMATION
EXTERIOR OIL WOODSTAIN CLEAR

SIZE:
0.75 l; 2.5 l; 5.0 l; 25 l

Product information provided above is based on current knowledge and is intended to advise the buyer/user to the best of our knowledge. However, this information must be adjusted/adapted individually to the areas of application and processing conditions. Unless we expressly guarantee the specific suitability or properties of products for a contractually specified purpose in writing, any application-related advice or information, even if provided to the best of our knowledge, shall be non-binding in all cases. In all other respects, our General Terms and Conditions of Sale and Delivery shall apply. Upon publication of a new version of this product information, the new information shall replace any previous product information.
For information specific to a certain country or region, please consult your local wholesaler or dealer:
OSMO UK,
Smeaton Close
Unit 24 Anglo Business Park
Aylesbury, Bucks HP19 8UP
Phone: 01296 481 220, www.osmouk.com

Version 09/26