Printing date 11.02.2022



### Safety data sheet

according to 1907/2006/EC, Article 31

Version number 15.6 (replaces version 15.4)

Revision: 11.02.2022

	SECTION 1: Identification of the substance/mixture and of the company/undertaking		
Article number:       3232 Clear satin; 3240 White transparent; 3262 Clear matt         1.2 Relevant identified uses of the substance or mixture and uses advised against Application of the substance       No further relevant information available.         Application of the substance       Paint Coating compound/ Surface coating/ paint         1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier:       Osmo Holz und Color GmbH & Co. KG Affhüppen Esch 12 D-48231 Warendorf Germany         Further information obtainable from:       Product safety department Tel.: +49 (0) 251 / 692 - 188 Fax: +49 (0) 251 / 692 - 462 e-mail: helmut.starp@osmo.de         1.4 Emergency telephone number:       emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory server	1 Product identifier		
1.2 Relevant identified uses         of the substance or mixture         and uses advised against         Application of the substance         / the mixture         Paint         Coating compound/ Surface coating/ paint         1.3 Details of the supplier of the safety data sheet         Manufacturer/Supplier:       Osmo Holz und Color GmbH & Co. KG         Affhüppen Esch 12         D-48231 Warendorf         Germany         Further information         obtainable from:         Product safety department         Tel.: +49 (0) 251 / 692 - 188         Fax: +49 (0) 251 / 692 - 462         e-mail: helmut.starp@osmo.de         1.4 Emergency telephone         number:       emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory server	ade name:	Polyx®-Oil Rapid	
Application of the substance       Paint         / the mixture       Paint         Coating compound/ Surface coating/ paint         1.3 Details of the supplier of the safety data sheet         Manufacturer/Supplier:       Osmo Holz und Color GmbH & Co. KG         Affhüppen Esch 12         D-48231 Warendorf         Germany         Further information         obtainable from:         Product safety department         Tel.: +49 (0) 251 / 692 - 188         Fax: +49 (0) 251 / 692 - 462         e-mail: helmut.starp@osmo.de         1.4 Emergency telephone         number:         emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory server	2 Relevant identified uses	3232 Clear satin; 3240 White transparent; 3262 Clear matt	
<ul> <li>Paint Coating compound/ Surface coating/ paint</li> <li>1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier:</li> <li>Osmo Holz und Color GmbH &amp; Co. KG Affhüppen Esch 12 D-48231 Warendorf Germany</li> <li>Further information obtainable from:</li> <li>Product safety department Tel.: +49 (0) 251 / 692 - 188 Fax: +49 (0) 251 / 692 - 462 e-mail: helmut.starp@osmo.de</li> <li>1.4 Emergency telephone number:</li> <li>emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory server</li> </ul>	nd uses advised against	No further relevant information available.	
Interviewed       Coating compound/ Surface coating/ paint         1.3 Details of the supplier of the safety data sheet         Manufacturer/Supplier:       Osmo Holz und Color GmbH & Co. KG         Affhüppen Esch 12         D-48231 Warendorf         Germany         Further information         obtainable from:         Product safety department         Tel.: +49 (0) 251 / 692 - 188         Fax: +49 (0) 251 / 692 - 462         e-mail: helmut.starp@osmo.de         1.4 Emergency telephone         number:         emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory server	oplication of the substance	9	
1.3 Details of the supplier of the safety data sheet         Manufacturer/Supplier:       Osmo Holz und Color GmbH & Co. KG         Affhüppen Esch 12       D-48231 Warendorf         Germany       Germany         Further information       obtainable from:         Product safety department       Tel.: +49 (0) 251 / 692 - 188         Fax: +49 (0) 251 / 692 - 462       e-mail: helmut.starp@osmo.de         1.4 Emergency telephone       emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory server	he mixture	Paint	
Manufacturer/Supplier:Osmo Holz und Color GmbH & Co. KG Affhüppen Esch 12 D-48231 Warendorf GermanyFurther information obtainable from:Product safety department Tel.: +49 (0) 251 / 692 - 188 Fax: +49 (0) 251 / 692 - 462 e-mail: helmut.starp@osmo.de1.4 Emergency telephone number:emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory server		Coating compound/ Surface coating/ paint	
Affhüppen Esch 12         D-48231 Warendorf         Germany         Further information         obtainable from:         Product safety department         Tel.: +49 (0) 251 / 692 - 188         Fax: +49 (0) 251 / 692 - 462         e-mail: helmut.starp@osmo.de         1.4 Emergency telephone         number:         emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory server	3 Details of the supplier of	the safety data sheet	
D-48231 Warendorf         Germany         Further information         obtainable from:       Product safety department         Tel.: +49 (0) 251 / 692 - 188         Fax: +49 (0) 251 / 692 - 462         e-mail: helmut.starp@osmo.de         1.4 Emergency telephone         number:       emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory server	anufacturer/Supplier:	Osmo Holz und Color GmbH & Co. KG	
Further information       Germany         obtainable from:       Product safety department         Tel.: +49 (0) 251 / 692 - 188         Fax: +49 (0) 251 / 692 - 462         e-mail: helmut.starp@osmo.de         1.4 Emergency telephone         number:       emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory server		Affhüppen Esch 12	
Further information         obtainable from:       Product safety department         Tel.: +49 (0) 251 / 692 - 188         Fax: +49 (0) 251 / 692 - 462         e-mail: helmut.starp@osmo.de         1.4 Emergency telephone         number:       emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory server		D-48231 Warendorf	
obtainable from:Product safety department Tel.: +49 (0) 251 / 692 - 188 Fax: +49 (0) 251 / 692 - 462 e-mail: helmut.starp@osmo.de1.4 Emergency telephone number:emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory server		Germany	
Tel.: +49 (0) 251 / 692 - 188         Fax: +49 (0) 251 / 692 - 462         e-mail: helmut.starp@osmo.de         1.4 Emergency telephone         number:         emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory server	<i>irther information</i>		
Fax: +49 (0) 251 / 692 - 462         e-mail: helmut.starp@osmo.de         1.4 Emergency telephone         number:       emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory server	otainable from:	Product safety department	
e-mail: helmut.starp@osmo.de <b>1.4 Emergency telephone</b> number: emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory server		Tel.: +49 (0) 251 / 692 - 188	
1.4 Emergency telephone number:emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory server		Fax: +49 (0) 251 / 692 - 462	
number: emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory serv		e-mail: helmut.starp@osmo.de	
	4 Emergency telephone		
German and English	ımber:	emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service German and English	

#### SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

2.2 Label elements Hazard pictograms



Signal word	Warning
Hazard statements	H226 Flammable liquid and vapour.
Precautionary statements	P101 If medical advice is needed, have product container or label at hand.
	P102 Keep out of reach of children.
	P210 Keep away from heat No smoking.
	P262 Do not get in eyes, on skin, or on clothing.
	P271 Use only outdoors or in a well-ventilated area.
	P501 Dispose of contents/container in accordance with national regulations.
Additional information:	3240: EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
	EUH210 Safety data sheet available on request.
	(Contd. on page 3

(Contd. on page 2)



#### according to 1907/2006/EC, Article 31

Printing date 11.02.2022

Version number 15.6 (replaces version 15.4)

Revision: 11.02.2022

### Trade name: Polyx®-Oil Rapid

	(Contd. of page 1)
2.3 Other hazards	Observe the general safety regulations when handling chemicals.
	Always wear a dust mask when sanding.
	Warning:
	Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)
	Must not be applied on the same spraying stand as lacquers or lacquer
	corrosives that contain NC (nitrocellulose). Risk of self-ignition.
Results of PBT and vP	/B assessment
PBT:	Not applicable.
vPvB:	Not applicable.

#### SECTION 3: Composition/information on ingredients

Description:	Mixture of substances listed below with nonhazardous additions.	
Dangerous componen	its:	
EC number: 918-481-9	aliphatic hydrocarbons, C10-C13	30–50%
	🚯 Asp. Tox. 1, H304, EUH066	
EC number: 927-241-2	aliphatic hydrocarbons, C9-C10	≥10–<20%
	♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ STOT SE 3, H336; Aquatic Chronic 3, H412	
CAS: 34590-94-8	Dipropylene glycol monomethyl ether	<2.5%
EINECS: 252-104-2	substance with a Community workplace exposure limit	
CAS: 13463-67-7	titanium dioxide - aerodynamic dia meter >10 μm	0-2.5%
EINECS: 236-675-5		
Additional information	<i>i:</i> The content of Titanium dioxide varies according to the colour sh	ade.
	Note 10: The classification as a carcinogen by inhalation applies	only to
	mixtures in powder form containing 1 % or more of titanium dioxi	de which is ii
	the form of or incorporated in particles with aerodynamic diamete	er ≤ 10 µm.
	For the wording of the listed hazard phrases refer to section 16.	

#### SECTION 4: First aid measures

4.1 Description of first aid General information:	Take affected persons out into the fresh air.
General mormation.	
After inhalation:	Supply fresh air; consult doctor in case of complaints.
After skin contact:	Immediately wash with water and soap and rinse thoroughly.
After eye contact:	Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
After swallowing:	If swallowed, seek medical advice immediately and show this container or label.
	(Contd. on page 3)



according to 1907/2006/EC, Article 31

Printing date 11.02.2022

Version number 15.6 (replaces version 15.4)

Revision: 11.02.2022

### Trade name: Polyx®-Oil Rapid

(Contd. of page 2)

Do NOT induce vomiting. 4.2 Most important symptoms

and effects, both acute and delayed Headache Dizziness

4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

#### SECTION 5: Firefighting measures

5.1 Extinguishing media	
Suitable extinguishing	
agents:	CO2, sand, extinguishing powder. Do not use water.
For safety reasons unsuitable	le
extinguishing agents:	Water with full jet
5.2 Special hazards arising	
from the substance or	
mixture	Formation of toxic gases is possible during heating or in case of fire.
5.3 Advice for firefighters	
Protective equipment:	No special measures required.
Additional information	Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.
	Cool endangered receptacles with water spray.

#### **SECTION 6: Accidental release measures**

6.1 Personal precautions, protective equipment and	
emergency procedures	Ensure adequate ventilation
	Wear protective equipment. Keep unprotected persons away.
	Wear protective clothing.
	Keep away from ignition sources.
6.2 Environmental	
precautions:	Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system.
6.3 Methods and material for	
containment and cleaning up	<b>ɔ:</b> Warm water and cleansing agent
	Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).
	Dispose of the material collected according to regulations.
	Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
	(Contd. on page 4)

Printing date 11.02.2022



### Safety data sheet

according to 1907/2006/EC, Article 31

Version number 15.6 (replaces version 15.4)

Revision: 11.02.2022

6.4 Reference to other	(Contd. of page Do not flush with water or aqueous cleansing agents
sections	See Section 7 for information on safe handling.
	See Section 8 for information on personal protection equipment.
	See Section 13 for disposal information.
SECTION 7: Handling an	d storage
7.1 Precautions for safe	
handling	Use only in well ventilated areas.
	Keep away from heat and direct sunlight.
	Keep receptacles tightly sealed.
	Prevent formation of aerosols.
	Open and handle receptacle with care.
General protective and	
hygienic measures:	Keep away from foodstuffs, beverages and feed.
	Immediately remove all soiled and contaminated clothing
	Store protective clothing separately.
	Do not inhale gases / fumes / aerosols.
Information about fire - and	
explosion protection:	Keep ignition sources away - Do not smoke.
	Protect against electrostatic charges.
	Keep respiratory protective device available.
	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
7.2 Conditions for safe storag Storage:	e, including any incompatibilities
Requirements to be met by	
storerooms and receptacles:	Store only in the original receptacle.
	Store in a cool location.
Information about storage in	
one common storage facility:	Not required.
Further information about	
storage conditions:	Keep container tightly sealed.
	Store in cool, dry conditions in well sealed receptacles.
Storage class:	3
7.3 Specific end use(s)	No further relevant information available. (Contd. on page



#### according to 1907/2006/EC, Article 31

Printing date 11.02.2022

Version number 15.6 (replaces version 15.4)

Revision: 11.02.2022

### Trade name: Polyx®-Oil Rapid

(Contd. of page 4)

#### SECTION 8: Exposure controls/personal protection 8.1 Control parameters Ingredients with limit values that require monitoring at the workplace: aliphatic hydrocarbons, C10-C13 TWA Short-term value: 1200 mg/m<sup>3</sup> **CEFIC-HSPA** 34590-94-8 Dipropylene glycol monomethyl ether IOELV Long-term value: 308 mg/m<sup>3</sup>, 50 ppm Skin **PNECs** 34590-94-8 Dipropylene glycol monomethyl ether PNEC sea water 190 mg/l PNEC fresh water 19 mg/l PNEC sewage treatment plant 4,168 mg/l PNEC fresh water 19 mg/l PENEC Sediment fresh water 70.2 mg/kg PNEC STP 4,168 mg/l PNEC Sediment marine water 190 mg/kg Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Appropriate engineering No further data; see item 7. controls Individual protection measures, such as personal protective equipment General protective and hygienic measures: Do not eat, drink, smoke or sniff while working. Do not carry product impregnated cleaning cloths in trouser pockets. Keep away from foodstuffs, beverages and feed. Avoid contact with the eyes and skin. Immediately remove all soiled and contaminated clothing Store protective clothing separately. Do not inhale gases / fumes / aerosols. Respiratory protection: Use suitable respiratory protective device only when aerosol or mist is formed. Use a properly fitted, air-purifying or air-fed repirator complying with an approved standard if a risk assessment indicates this is necessary. Half mask with round thread connection EN 148-1 (screw-on filter) and combination filter A1 - P2 according to German DIN EN 14387. Not necessary if room is well-ventilated. In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective

device.

(Contd. on page 6)

FU



according to 1907/2006/EC, Article 31

Version number 15.6 (replaces version 15.4)

Revision: 11.02.2022

# Trade name: Polyx®-Oil Rapid

Printing date 11.02.2022

	(Contd. of page 5)
Hand protection	Protective gloves
	The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
	Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
Material of gloves	The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
Penetration time of glove	
material	The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
For the permanent contact	
gloves made of the following	
materials are suitable:	Nitrile rubber, NBR
	Recommended thickness of the material: > 0.4 mm
	For the mixture of chemicals mentioned below the penetration time has to be
	at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).
As protection from splashes	, , , , , , , , , , , , , , , , , , ,
gloves made of the following	
materials are suitable:	Nitrile rubber, NBR
Eye/face protection	Tightly sealed goggles
Body protection:	Protective work clothing

### SECTION 9: Physical and chemical properties

9.1 Information on basic physical and c	hemical properties	
General Information		
Physical state	Fluid	
Colour:	According to product specification	
Odour:	Mild	
Melting point/freezing point:	Undetermined.	
Boiling point or initial boiling point and	boiling	
range	> 144 °C	
Lower and upper explosion limit		
Lower:	0.7 Vol %	
Upper:	6.0 Vol %	
Flash point:	45-52 °C (DIN EN ISO 2719)	
Auto-ignition temperature:	Product is not selfigniting.	
рН	Not applicable	
	(Contd. on n	

(Contd. on page 7)

<sup>-</sup> EU -



#### according to 1907/2006/EC, Article 31

Printing date 11.02.2022

Version number 15.6 (replaces version 15.4)

Revision: 11.02.2022

### Trade name: Polyx®-Oil Rapid

Vie e e e itere		
Viscosity:		
Kinematic viscosity at 20	<b>℃</b>	25-45 s (DIN EN ISO 2431/4mm)
		>21 mm²/s (40°C) (calculated)
Dynamic:		Not determined.
Solubility		
water:		Not miscible or difficult to mix.
Vapour pressure at 20 °C		10 hPa
Density and/or relative de	ensity	
Density at 20 °C:		0.88-0.95 g/cm³ (DIN 51757)
9.2 Other information		
Appearance:		
Form:		Fluid
Important information on		nd
environment, and on safe	ety.	
Ignition temperature:		240 °C
Explosive properties:		Product is not explosive. However, formation of
		explosive air/vapour mixtures are possible.
Solvent content:		
VOC (EC)		< 500 g/l (VOC-max. Cat A/i (2010) = 500 g/l)
Information with regard t		
	o prysical nazaro clas	Ses
_	o physical nazard clas	Ses
Explosives	o pnysical nazaro cias Void	Ses
Explosives		Ses
_		Ses
Explosives		Ses
Explosives	Void	Ses
Explosives Flammable gases	Void	Ses
Explosives Flammable gases Aerosols	Void Void	Ses
Explosives Flammable gases	Void Void	Ses
Explosives Flammable gases Aerosols	Void Void	Ses
Explosives Flammable gases Aerosols	Void Void Void	Ses
Explosives Flammable gases Aerosols Oxidising gases	Void Void Void Void	Ses
Explosives Flammable gases Aerosols Oxidising gases Gases under pressure	Void Void Void	Ses
Explosives Flammable gases Aerosols Oxidising gases	Void Void Void Void	Ses
Explosives Flammable gases Aerosols Oxidising gases Gases under pressure	Void Void Void Void Void	
Explosives Flammable gases Aerosols Oxidising gases Gases under pressure	Void Void Void Void	
Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids	Void Void Void Void Void Flammable liquid a	
Explosives Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids	Void Void Void Void Void	



according to 1907/2006/EC, Article 31

Printing date 11.02.2022

Version number 15.6 (replaces version 15.4)

Revision: 11.02.2022

# Trade name: Polyx®-Oil Rapid (Contd. of page 7) Self-reactive substances and mixtures Void **Pyrophoric liquids** Void **Pyrophoric solids** Void Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water Void **Oxidising liquids** Void **Oxidising solids** Void Organic peroxides Void Corrosive to metals Void **Desensitised explosives** Void

### SECTION 10: Stability and reactivity

10.1 Reactivity

No further relevant information available.

Page 9/14



### Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.02.2022

Version number 15.6 (replaces version 15.4)

Revision: 11.02.2022

### Trade name: Polyx®-Oil Rapid

	(Contd. of page 8)
10.2 Chemical stability	
Thermal decomposition /	
conditions to be avoided:	No decomposition if used according to specifications.
10.3 Possibility of hazardous	
reactions	Reacts with fabric soaked in the product (e.g. cleaning wool).
10.4 Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
10.5 Incompatible materials:	No further relevant information available.
10.6 Hazardous	
decomposition products:	Carbon monoxide and carbon dioxide
	Nitrogen oxides (NOx)
Additional information:	Warning: Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)

#### **SECTION 11: Toxicological information**

## 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity Based on available data the classification criteria are not met

Acute toxicity		Based on available data, the classification criteria are not met.		
LD/LC50 values relevant for classification:				
aliphatic hydrocarbons, C10-C13				
Oral	LD50	>5,000 mg/kg (rat)		
Dermal	LD50	>5,000 mg/kg (rat)		
Inhalative	LC50 / 4h	>5 mg/l (rat)		
aliphatic hydrocarbons, C9-C10				
Oral	LD50	>2,000 mg/kg (rat)		
Dermal	LD50	>2,000 mg/kg (rat)		
Inhalative	LC50 / 4h	>20 mg/l (rat)		
34590-94-8 Dipropylene glycol monomethyl ether				
Oral	LD50	>5,000 mg/kg (rat)		
Dermal	LD50	>19,020 mg/kg (rat)		
		13,000–14,000 mg/kg (rabbit)		
Inhalative	LC50 / 4h	1,667 mg/l (rat)		
	LC50 / 72h	0.76 mg/l (selenastrum capricornutum)		
Skin corro	osion/irritat	<i>ion</i> Based on available data, the classification criteria are not met.		
Serious e	ye damage/	<i>irritation</i> Based on available data, the classification criteria are not met.		
Respirato	ry or skin			
sensitisation		Based on available data, the classification criteria are not met.		
Germ cell mutagenicity		<i>ity</i> Based on available data, the classification criteria are not met.		
Carcinogenicity		Based on available data, the classification criteria are not met.		
Reproductive toxicity		<ul> <li>Based on available data, the classification criteria are not met.</li> </ul>		
			(Contd. on page 1	

Page 10/14



### Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.02.2022

Version number 15.6 (replaces version 15.4)

Revision: 11.02.2022

### Trade name: Polyx®-Oil Rapid

			(Contd. of page 9)	
STOT-singl	e exposure	Based on available data, the classification criteria are not met.		
STOT-repe	ated exposure	Based on available data, the classification criteria are not met.		
Aspiration		Based on available data, the classification criteria are not met.		
11.2 Inform	ation on other haz	ards		
Endocrine	disrupting propert	ies		
None of the	ingredients is listed			
SECTION 12: Ecological information				
12.1 Toxicity				
Aquatic tox	cicity:			
aliphatic hy	drocarbons, C10-0	C13		
EC50 / 48h	>1,000 mg/l (Daphi	nia magna)		
IC50 / 72h	>1,000 mg/l (algae)	)		
LC50 / 96h	>1,000 mg/l (fish)			
aliphatic hy	drocarbons, C9-C	10		
EC50 / 24h	<130 mg/l (Oncorh	ynchus mykiss (Regenbogenforelle))		
	>100 mg/l (selenas	strum capricornutum)		
34590-94-8	Dipropylene glyco	I monomethyl ether		
EC50 / 48h	70.2 mg/l			
	1,919 mg/l (Daphni	ia magna)		
LC50 / 96h	5.3 mg/l (Oncorhynchus mykiss (Regenbogenforelle))			
LC50 / 48h	10.2 mg/l (Oncorhynchus mykiss (Regenbogenforelle))			
12.2 Persis	tence and			
degradabili	-	No further relevant information available.		
12.3 Bioaco	cumulative			
potential		No further relevant information available.		
12.4 Mobilit	•	No further relevant information available.		
	s of PBT and vPvE			
PBT:		Not applicable.		
vPvB:		Not applicable.		
12.6 Endoc properties	rine disrupting	The product does not contain substances with endocrine disrup	ting properties	
	adverse effects		ning properties.	
	ecological informa	ntion:		
General no	-	Water hazard class 1 (German Regulation) (Self-assessment):	slightly	
		hazardous for water	Contd. on page 11)	



according to 1907/2006/EC, Article 31

Printing date 11.02.2022

Version number 15.6 (replaces version 15.4)

Revision: 11.02.2022

### Trade name: Polyx®-Oil Rapid

(Contd. of page 10)

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

 Recommendation
 Must not be disposed together with household garbage. Do not allow product to reach sewage system.

08 01 11<sup>\*</sup> waste paint and varnish containing organic solvents or other hazardous substances 15 01 10<sup>\*</sup> packaging containing residues of or contaminated by hazardous substances

Uncleaned packaging: Recommendation:

Disposal must be made according to official regulations.

#### **SECTION 14: Transport information**

14.1 UN number or ID number	
ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name	
ADR	1263 PAINT
IMDG, IATA	PAINT
14.3 Transport hazard class(es)	
ADR	
Class	3 (F1) Flammable liquids.
Label	3
IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30
EMS Number:	F-E, <u>S-E</u>
Stowage Category	A
14.7 Maritime transport in bulk according to IM	10
instruments	Not applicable.
	(Contd. on page



### according to 1907/2006/EC, Article 31

Printing date 11.02.2022

Version number 15.6 (replaces version 15.4)

Revision: 11.02.2022

### Trade name: Polyx®-Oil Rapid

	(Contd. of pa
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1263 PAINT, 3, III

#### SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

<i>Directive 2012/18/EU Named dangerous</i>		
substances - ANNEX I	None of the ingredients is listed.	
Seveso category	P5c FLAMMABLE LIQUIDS	
Qualifying quantity (tonnes)		
for the application of lower-		
tier requirements	5,000 t	
Qualifying quantity (tonnes)		
for the application of upper-		
tier requirements	50,000 t	
REGULATION (EC) No		
1907/2006 ANNEX XVII	Conditions of restriction: 3	
DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II		
None of the ingredients is listed		
REGULATION (EU) 2019/1148		
Annex I - RESTRICTED EXPL under Article 5(3))	OSIVES PRECURSORS (Upper limit value for the purpose of licensing	
None of the ingredients is listed		
	(Contd. on page 13)	



#### according to 1907/2006/EC, Article 31

Version number 15.6 (replaces version 15.4)

Revision: 11.02.2022

(Contd. of page 12)

Printing date 11.02.2022

### Trade name: Polyx®-Oil Rapid

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

#### Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

National regulations: GISBAU-Code VOC (EC) 15.2 Chemical safety assessment:

GISCODE: Ö60 < 500 g/l (VOC-max. = 500 g/l (2010 A/i))

A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

<i>Reasons for alterations Relevant phrases</i>	Formal ChangesH226Flammable liquid and vapour.H304May be fatal if swallowed and enters airways.H336May cause drowsiness or dizziness.H412Harmful to aquatic life with long lasting effects.EUH066Repeated exposure may cause skin dryness or cracking.
Department issuing SDS:	product safety department
Contact:	Hr. Dr. Starp
Version number of previous	
version:	15.4
Abbreviations and acronyms:	ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3 (Contd. on page 14)



#### according to 1907/2006/EC, Article 31

Printing date 11.02.2022

Version number 15.6 (replaces version 15.4)

Revision: 11.02.2022

(Contd. of page 13)

### Trade name: Polyx®-Oil Rapid

Sources

Safety data sheets from raw material suppliers ECHA Portal ESIS : European chemical Substances Information System

EU -