

Printing date 23.05.2018 Version number 14 Revision: 11.05.2018

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: 4006 Osmo Wood Protector, Clear

1.2 Relevant identified uses of the substance or mixture and uses

advised against No further relevant information available.

Application of the substance / the

*mixture* Priming

Coating compound/ Surface coating/ paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG

Affhüppen Esch 12 D-48231 Warendorf

Further information obtainable

*from:* Product safety department

Phone: +49 (0) 251 / 692 - 188 Fax: +49 (0) 251 / 692 - 462 e-mail: helmut.starp@osmo.de

1.4 Emergency telephone

number: emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German

and English

#### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to

Regulation (EC) No 1272/2008 The product is not classified, according to the CLP regulation.

2.2 Label elements

Labelling according to Regulation

(EC) No 1272/2008 Void
 Hazard pictograms Void
 Signal word Void
 Hazard statements Void

**Precautionary statements** Although this product is not subject to identification regulations, we recommend that

the safety suggestions are observed. Keep out of reach of children.

If medical advice is needed, have product container or label at hand.

P262 Do not get in eyes, on skin, or on clothing. P271 Use only outdoors or in a well-ventilated area.

Additional information: Safety data sheet available on request.

Information concerning

particular hazards for human and

*environment:* Observe the general safety regulations when handling chemicals.

Always wear a dust mask when sanding.

(Contd. on page 2)



Printing date 23.05.2018 Version number 14 Revision: 11.05.2018

### Trade name: 4006 Osmo Wood Protector, Clear

(Contd. of page 1)

30-60%

2.3 Other hazards Warning:

Wash out any used cloth impregnated with this product immediately after use or store

in an airtight container (danger of self-ignition)

Results of PBT and vPvB assessment

*PBT:* Not applicable. *vPvB:* Not applicable.

#### SECTION 3: Composition/information on ingredients

3.2 Mixtures

**Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:

EC number: 918-481-9 aliphatic hydrocarbons, C10-C13

Index number: 649-327-00-6 Reg.nr.: 01-2119457273-39

Additional information: For the wording of the listed hazard phrases refer to section 16.

#### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

After inhalation: Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult

doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: If swallowed, seek medical advice immediately and show this container or label.

4.2 Most important symptoms and

effects, both acute and delayed Dizziness

Headache

4.3 Indication of any immediate medical attention and special

treatment needed No further relevant information available.

#### **SECTION 5: Firefighting measures**

5.1 Extinguishing media

Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant

foam.

(Contd. on page 3)



Printing date 23.05.2018 Version number 14 Revision: 11.05.2018

### Trade name: 4006 Osmo Wood Protector, Clear

(Contd. of page 2)

For safety reasons unsuitable

extinguishing agents: Water with full jet

5.2 Special hazards arising from

the substance or mixture Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

**Protective equipment:** Mouth respiratory protective device.

Additional information Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official

regulations.

#### SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and

*emergency procedures* Ensure adequate ventilation

Keep away from ignition sources.

6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for

containment and cleaning up: Warm water and cleansing agent

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

**6.4 Reference to other sections** See Section 13 for disposal information.

No dangerous substances are released.

#### SECTION 7: Handling and storage

7.1 Precautions for safe handling Use only in well ventilated areas.

Keep receptacles tightly sealed.

Keep away from heat and direct sunlight.

Prevent formation of aerosols.

Information about fire - and

*explosion protection:* Keep ignition sources away - Do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by

storerooms and receptacles: Store only in the original receptacle.

Store in a cool location.

Information about storage in one

common storage facility: Do not store together with alkalis (caustic solutions).

Do not store together with oxidising and acidic materials.

Further information about

storage conditions: Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 4)



Printing date 23.05.2018 Version number 14 Revision: 11.05.2018

### Trade name: 4006 Osmo Wood Protector, Clear

(Contd. of page 3)

7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

Additional information about

design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

aliphatic hydrocarbons, C10-C13

TWA (8 H) Long-term value: 1.000 mg/m<sup>3</sup>, 150 ppm ppm

Source: UK SIA

**Additional information:** The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment: General protective and hygienic

*measures:* Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

Immediately remove all soiled and contaminated clothing

Keep away from foodstuffs, beverages and feed.

Avoid contact with the eyes and skin.

**Respiratory protection:** Not necessary if room is well-ventilated.

Use suitable respiratory protective device only when aerosol or mist is formed.

Short term filter device:

Gas filter EN 14387 Type A (organic gas / vapor (boiling point > 65 ° C)).

**Protection of hands:** Protective gloves

To avoid skin problems reduce the wearing of gloves to the required minimum.

Selection of the glove material on consideration of the penetration times, rates of

diffusion and the degradation

Material of gloves Nitrile rubber, NBR

Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective

gloves and has to be observed.

For the permanent contact gloves made of the following materials

are suitable: Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.4$  mm

For the permanent contact of a maximum of 15 minutes gloves made of the following materials

are suitable: Nitrile rubber, NBR

As protection from splashes gloves made of the following

materials are suitable: Nitrile rubber, NBR

Eye protection: Goggles recommended during refilling

(Contd. on page 5)



Printing date 23.05.2018 Version number 14 Revision: 11.05.2018

Trade name: 4006 Osmo Wood Protector, Clear

(Contd. of page 4)

**Body protection:** Protective work clothing

#### SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

**General Information** 

Appearance:

Form: Viscous
Colour: Colourless
Odour: Mild

Change in condition

*Melting point/freezing point:* Undetermined. *Initial boiling point and boiling range:* > 180 °C

Flash point: > 61 °C (DIN EN ISO 2719)

*Ignition temperature:* 240 °C

Auto-ignition temperature: Product is not selfigniting.

Explosive properties: Product does not present an explosion hazard.

Explosion limits:

 Lower:
 0.6 Vol %

 Upper:
 7.0 Vol %

**Density at 20 °C:** 0.8 - 0.9 g/cm³ (DIN 51757)

Solubility in / Miscibility with

water: Not miscible or difficult to mix.

Viscosity:

Dynamic: Not determined.

**Kinematic at 20 °C:** 25 - 35 s (DIN 53211/4)

> 30 s (ISO 3mm)

Solvent content:

VOC (EC)
 < 750 g/l (VOC-max. = 750 g/l (2010 A/h))</li>
 9.2 Other information
 No further relevant information available.

#### SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability
Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 6)



Printing date 23.05.2018 Version number 14 Revision: 11.05.2018

### Trade name: 4006 Osmo Wood Protector, Clear

(Contd. of page 5)

10.3 Possibility of hazardous

reactions Reacts with fabric soaked in the product (e.g. cleaning wool).

10.4 Conditions to avoid No further relevant information available.10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition

products: Formation of toxic gases is possible during heating or in case of fire.

Nitrogen oxides (NOx)

Carbon monoxide and carbon dioxide

Additional information:

Warning:

Wash out any used cloth impregnated with this product immediately after use or store

in an airtight container (danger of self-ignition)

#### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50	LD/LC50 values relevant for classification:		
aliphatic l	aliphatic hydrocarbons, C10-C13		
Oral	LD50	> 5000 mg/kg (rat) (OECD 401)	
Dermal	LD50	> 5000 mg/kg (rat) (OECD 402)	
Inhalative	LC50 / 4h	21 mg/l (rat) (OECD 403)	

Primary irritant effect:

Skin corrosion/irritation At long or repeated contact with skin it may cause dermatitis due to the degreasing

effect of the solvent.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicityBased on available data, the classification criteria are not met.CarcinogenicityBased on available data, the classification criteria are not met.Reproductive toxicityBased on available data, the classification criteria are not met.STOT-single exposureBased on available data, the classification criteria are not met.STOT-repeated exposureBased on available data, the classification criteria are not met.Aspiration hazardBased on available data, the classification criteria are not met.

#### SECTION 12: Ecological information

#### 12.1 Toxicity

Aquatic toxicity:		
aliphatic hydroc	arbons, C10-C13	
EC50 / 48h	> 1000 mg/l (daphnia) (OECD 202)	
		(0 1

(Contd. on page 7)



Printing date 23.05.2018 Version number 14 Revision: 11.05.2018

### Trade name: 4006 Osmo Wood Protector, Clear

(Contd. of page 6)

EC50/ 72h > 1000 mg/l (algae) (OECD 201) LC50 / 96h > 1000 mg/l (fish) (OECD 203)

Biolog. Abbaubarkeit (leicht abbaubar)

12.2 Persistence and degradability No further relevant information available.
 12.3 Bioaccumulative potential No further relevant information available.
 12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for

water

12.5 Results of PBT and vPvB assessment

*PBT*: Not applicable.*vPvB*: Not applicable.

12.6 Other adverse effects No further relevant information available.

### SECTION 13: Disposal considerations

13.1 Waste treatment methods

**Recommendation** Must not be disposed together with household garbage. Do not allow product to reach

sewage system.

European waste catalogue	
08 01 11	waste paint and varnish containing organic solvents or other dangerous substances
15 01 10	packaging containing residues of or contaminated by dangerous substances

Uncleaned packaging:

**Recommendation:** Disposal must be made according to official regulations.

Recommended cleansing agents: Solvent naphtha

CECTION	1 / T	, · · ·
	14. Tranch	ort information
SECTION	IT. II UII SU	ori iniormation

14.1 UN-Number ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	
14.4 Packing group		
ADR, IMDG, IATA	Void	

(Contd. on page 8)



Printing date 23.05.2018 Version number 14 Revision: 11.05.2018

### Trade name: 4006 Osmo Wood Protector, Clear

(Contd. of page 7)

		(
14.5 Environmental hazards:		
Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Transport in bulk according to Annex I		
and the IBC Code	Not applicable.	
UN ''Model Regulation'':	Void	

#### SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations:

GISBAU-Code GISCODE: M-GF02

VOC (EC) < 750 g/l (VOC-max. = 750 g/l (2010 A/h))

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Relevant phrases** H304 May be fatal if swallowed and enters airways.

**Department issuing SDS:** product safety department

Contact: Hr. Dr. Starp

Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement

concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Asp. Tox. 1: Aspiration hazard – Category 1

GE