



A Performance Partnership



THE RIGHT PROTECTION...

Country Colour



- Extremely weather & UV resistant
- Very water & dirt resistant
- Microporous, breathable finish
- No sanding necessary for future applications
- Opaque finish
- 19 colours to choose from





Natural Oil Woodstain



- Wood grain remains visible
- Durable & hardwearing
- Very water & dirt resistant
- Resists the development of algae, mildew & fungal attack
- Microporous, breathable finish
- No sanding necessary for future applications
- 19 colours to choose from

*Osmo UV-Protection may be used.
However, please contact your local
stockist regarding application.*

...WITH OSMO UK

End Grain Sealing Wax & WR Base Coat



End Grain Sealing Wax:

- Protects end grain

WR Base Coat

- Protects against blue stain rot & mildew
- Unique combination of oil & water that reduces swelling & shrinking and enhances performance

Protecting Accoya from Fungi & Blue Stain

We strongly recommend to apply End Grain Sealing Wax & WR Basecoat to Accoya.

Before coating, Accoya wood should be clean, dry (below 8% mc) & free of dust, grease & other pollution.

Protecting Accoya® Timber

NATURAL INGREDIENTS

The foundation of Osmo wood finishes has been based upon purified and refined natural resources which are carefully harvested natural oils and hard waxes.

HIGH COVERAGE

With just one tin of Osmo you can achieve near to double the square meter coverage of an ordinary finishing system, saving you time and money.



MICROPOROUS

The wood remains microporous and continues to absorb and release water without damage. The surface can breathe and becomes anti-static, which attracts less dust and dirt.

MAINTENANCE

Forget about time consuming, tiring sanding. Osmo natural wood finishes can easily be renovated at any time without the need for sanding.

Osmo can be applied to the following:
Facades (cladding), garden fencing, garden
buildings, structures & decking.

Care for your treated Accoya exterior
products should be managed in line with
exposure, use and wear & tear.

Osmo recommends annual inspection &
subsequent redecoration works depending
on wear. By appropriately topping up the
surface at the correct time the Osmo coating
performance remains optimal.

For further advice please contact Osmo.

Osmo UK

01296 481220

sales@osmouk.com

www.osmouk.com

